



Generator set	Type	Open	Open with ATS	Super Silent	Super Silent with ATS
	Genset Model	CK32000	CK32000A	CK32000SS	CK32000SSA
	Prime Power Rating	250KVA/200KW			
	Standby Power Rating	275KVA/220KW			
	Size(mm)	2650*1050*1540		3800*1300*1900	
	Weight(KG)	2150		3380	
	Internal protection	IP22			
	Rate current(A)	361			
	Specific Fuel Consumption(L/H)@100% Load	35.7			
	Noise at 7 meters away(dB)	N/A		75dB	
Engine	Model	Cummins MTA11-G2 / 6LTAA8.9-G2			
	NO. of Cylinder	6			
	Cylinder Type	L			
	RPM	1500			
	Bore (mm)	114			
	Stroke(mm)	135			
	Speed Governor	electronic			
	Start system(VDC)	24			
	Lub Oil Specification	15W40			
	Displacement(Ltrs)	8.9			
	Lub Oil Sump Capacity(Ltrs)	23.8			
	Coolant Capacity(Ltrs)	24.3			
	Air inspiration	turbo			
	Phase	3			
	Alternator	Brand	EVO		
Model		TCU288F			
3 Phase Voltage(1 Phase) Volts		380-415(220-240)			
RPM/Frequency		1500rpm/50hz			
Power Factor(%)		0.8(lagging)			
Voltage Tolerance(+/- %)		1			
Insulation Class		H			
Control Panel		Brand	KUSING		
	Model	AD6132			
Fuel Tank	Capacity(Ltrs)	SUPPORT TO RUN 8 TO 10 HOURS			