



Generator set	Type	Open	Open with ATS	Silent	Silent with ATS
	Genset Model	CK32200	CK32200A	CK32200S	CK32200SA
	Prime Power Rating	275KVA/220KW			
	Standby Power Rating	312.5KVA/250KW			
	Size(mm)	2850*1050*1580		4200*1400*2100	
	Weight(KG)	2860		3500	
	Internal protection	IP22			
	Rate current(A)	396			
	Specific Fuel Consumption(L/H)@100% Load	39			
Noise at 7 meters away(dB)	N/A		75db		
Engine	Model	CUMMINS 6LTAA9.5-G3/QSM11-G2 / NTA855-G1A			
	NO. of Cylinder	6			
	Cylinder Type	L			
	RPM	1500			
	Bore (mm)	140			
	Stroke(mm)	152			
	Speed Governor	electronic			
	Start system(VDC)	24			
	Lub Oil Specification	15W40			
	Displacement(Ltrs)	14			
	Lub Oil Sump Capacity(Ltrs)	38.6			
	Coolant Capacity(Ltrs)	63.9			
	Air inspiration	turbo			
	Phase	3			
Alternator	Brand	EVO			
	Model	TCU288G			
	3 Phase Voltage(1 Phase) Volts	380-415(220-240)			
	RPM/Frequency	1500rpm/50hz			
	Power Factor(%)	0.8(lagging)			
	Voltage Tolerance(+/- %)	1			
	Insulation Class	H			
Control Panel	Brand	KUSING			
	Model	AD6132			
Fuel Tank	Capacity(Ltrs)	352			