




Generator set	Type	Open	Open with ATS	Silent	Silent with ATS
	Genset Model	CK35200	CK35200A	CK35200S	CK35200SA
	Prime Power Rating	650KVA/520KW			
	Standby Power Rating	715KVA/572KW			
	Size(mm)	3650*1500*2050		5000*1800*2550	
	Weight(KG)	4900		5900	
	Internal protection	IP22			
	Rate current(A)	938			
	Specific Fuel Consumption(L/H)@100% Load	98			
	Noise at 7 meters away(dB)	N/A		75db	
Engine	Model	Cummins QSKT19-G4			
	NO. of Cylinder	6			
	Cylinder Type	L			
	RPM	1500			
	Bore (mm)	159			
	Stroke(mm)	159			
	Speed Governor	electronic			
	Start system(VDC)	24			
	Lub Oil Specification	15W40			
	Displacement(Ltrs)	18.9			
	Lub Oil Sump Capacity(Ltrs)	50			
	Coolant Capacity(Ltrs)	95			
	Air inspiration	turbo			
	Phase	3			
Alternator	Brand	EVO			
	Model	TCU368E			
	3 Phase Voltage(1 Phase) Volts	380-415(220-240)			
	RPM/Frequency	1500rpm/50hz			
	Power Factor(%)	0.8(lagging)			
	Voltage Tolerance(+/- %)	1			
	Insulation Class	H			
Control Panel	Brand	KUSING			
	Model	AD6132			
Fuel Tank	Capacity(Ltrs)	SUPPORT 8-10 HOURS RUNNING TIME			